	INFOR	mation f	REPORT	CD NO.	-		
COUNTRY	Yugoslavia	CONFIDE	NTIAL	DATE DISTR. 29 Aug 5	50X1-HUN		
SUBJECT	Aluminium Factory at S	trnisce	NC. OF PAGES 1				
PLACE ACQUIRED				NO. OF ENCLS.	50X1-HUN		
DATE OF INFO							
OF THE CHITED S U.S.C., SI AND 3 OF ITE CONTENTS	CONTAINS (MFORMATION APPECTING VILL MATIOUS) DE MATION D	LATION	THIS IS UNEV.	ALUATED INFORMATION	50X1-HUN		

- b. The material is then mixed in tanks with a solution of sodium hydroxide (NaOH).
- c. It is then treated in autoclaves to form sodium alaminate.
- d. The charge is then transferred to settling tanks for the removal of insoluble residue consisting mainly of ferric oxide, silica and an insoluble sodium-aluminium silicate.
- e. The aluminate solution is decanted, diluted, clarified and filtered, and finally run into decomposing tanks in which a small amount of Al(OH)3 is added and stirred. The Al(OH)3 is precipitated from the solution with regeneration of NaOH.
- f. The pulp is thickened, filtered and washed.
- g. Al(OH)3 is calcined to produce Al2O3.
- 2. The production capacity of the Strnisce factory is 55,000 tons of aluminium oxide per year. Approximately 30,000 kws of electrical energy will be consumed in the electrolysis of aluminium oxide.

		-	CLAS	SIFICATI	ON	SECRE'	t/conit	OL - I	U.S. OF	FICIAI	s only	ge stations a delegate access	and the said of th	
STATE	12	NAVY		NSRB		DIST	RIBUTION							i
ARMY		AIR		9		.								
٠.	•			c	ONE			. 1						
	COR			ONE				Documen						